

...без езикови бариери!!!

Translation from Bulgarian language

Sheet 1 of 2

Republic of Bulgaria, 1618 Sofia, 86 "N. Petkov" blvd. Phone: (3592) 855 50 57; Fax: (3592) 955 96 38 e-mail: nisi@nisi.bg, web:www.nisi.bg

## TEST CENTER FOR CONSTRUCTION (TCC) at NISI EOOD

ACCREDITED UNDER BDS EN ISO / IEC 17025: 2018 Certificate reg. No. 88 ЛИ/24.03.2020, issued by EA BAS with validity until 01.10.2022

Sector: "Concretes and reinforcements, construction materials and products"

## TEST REPORT

No. 47-1-36/15.02.2021

*Name of product:* Covers for gullies and manholes - square covers with frame and lock made of polymer composite with nominal dimensions of the clear opening 400/400 mm, class B 125

Manufacturer:

"Reco Production"Ltd

Contracting entity:

"Reco Production"Ltd

town of Novi Iskar, 27 "Ravnets" str.

application from 19.01.2021

## Test method:

BDS EN 124-1: 2015 "Gully tops and manhole tops for vehicular and pedestrian areas. Part 1: Definitions, classification, general principles of design, performance requirements and test methods"

Date of receipt of the sample and ICS: entry No. 47/19.01.2021

Number of test pieces:

1 piece complete with the frame, taken and presented by the

Contracting entity

*Test period:* 19.01.2021 – 05.02.2021

ICS Director:

/As.Prof.Eng.Tsv.Gyurova/

The results only apply to the tested samples. Extracts from the report may not be reproduced without the written consent the Construction Testing Center - TCC-NISI EOOD.

Галиана – ТТ ООД, гр. Русе, ул. Сърнена гора 44, тел./факс: 082 87 60 29, e-mail: prevodi@galiana.bg, www.galiana.bg

## TEST RESULTS:

No	Type of test / characteristic	Unit of measure	Test method	No. and identification of the sample	Test result, uncertainty	Limit values according to specification / standard 3)	Test conditions
1	2	3	4	5	6	7	8
1.	Residual deformation <sup>1)</sup>	mm	BDS EN 124-1: 2015	36	0,8	≤ <b>4,0</b> <sup>2)</sup>	(19±2)°C (59±2)%RH
2.	Test load	-			Withstands the load without occurrence of cracks  Destruction by force of 142,3 kN	Cracks are not allowed to appear under a load of 125 kN for 30 s	

Notes:

1) After applying 2/3 of the test load strength - 2/3 of 125 kN = 83.3 kN.

2) The permissible residual deformation is equal to the clear hole (CO) / 100.

3) According to BDS EN 124-1: 2015 for class B 125.

Test performed by:

/techn.Y.Yordanov/

Head of Sector:

ICS Director:

/As.Prof.Eng. E. Penev/

/As.Prof.Eng. Tsv. Gyurova/

I, Galina Stoyanova, hereby certify that to the best of my knowledge this is a true and accurate translation from Bulgarian into English of the attached document. The translation consists of 2 /two/ pages. Mruce

Galina Tosheva Ancheva-Stoyanova